

Xerox® VersaLink® C400 Color Printer

VersaLink® C400 Color Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® C400
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 36 ppm color and black-and-white Up to 35 ppm color and black-and-white Up to 30 ppm color and black-and-white
Two-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 24 ppm color and black-and-white Up to 23 ppm color and black-and-white Up to 21 ppm color and black-and-white
Monthly Duty Cycle²	Up to 85,000 pages/month
Recommended Average Monthly Print Volume³	Up to 8,500 pages
Processor	1.05GHz ARM Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11 n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC+/- 10% Frequency: 50/60 Hz+/- 3Hz, 10 A			
Europe and Other Geographies	Voltage: 220-240 VAC+/- 10% Frequency: 50/60 Hz+/- 3Hz, 6 A			
POWER CONSUMPTION				
Continuous Printing⁴	705 watts or less			
Ready/Standby Mode⁴	76 watts or less			
Energy Saver/Sleep Mode⁴	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° F to 95° F/0° C to 35° C			
Required Temperature Range (Operating)	50° F to 90° F/10° C to 32° C			
Required Relative Humidity	10% to 85 %			
Sound Power Levels Operating Standby	6.88 B(A) or less 5.0 B(A) or less			
Sound Pressure Levels Operating Standby	53.1 dB(A) or less 29.2 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 6 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C400	19.3 in./491 mm	19.2 in./488 mm	15.7 in./399 mm	57 lb./26 kg
550-sheet Paper Tray	16.8 in./427 mm	19.1 in./485 mm	5.4 in./138 mm	8.6 lb./3.9 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C400	24.7 in./627 mm	25.1 in./638 mm	20.7 in./526 mm	67.13 lb./30.45 kg
550-sheet Paper Tray	23.2 in./590 mm	21.4 in./544 mm	9.5 in./241 mm	11.7 lb./5.3 kg
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE				
Certifications	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .			
PRINT				
First-Print-Out Time	As fast as 9.3 seconds color/8.2 seconds black-and-white			
Print Resolution	Up to 600 x 600 x 8 dpi (enhanced)			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			

Xerox® VersaLink® C400 Color Printer

<p>Print Features</p>	<p>Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings</p>
<p>Print from USB</p>	<p>Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p>Operating Systems</p>	<p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.</p>
<p>Fonts</p>	<p>PostScript fonts: 136 PCL fonts: 83</p>
<p>Xerox® Global Print Driver®</p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p>Xerox® Pull Print Driver</p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Easy Assist App	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
SECURITY	
Security Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM) <p>*Requires HDD/Productivity Kit</p>

ACCOUNTING	
XEROX® STANDARD ACCOUNTING TOOL/NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)</p>
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements include simultaneous support for HTTP/HTTPS protocols • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party NetworkingAccount
PAPER HANDLING	
BYPASS TRAY	
Capacity⁵	150 sheets
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76.2 x 127 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Labels Envelopes Custom
TRAY 1	
Capacity⁵	550 sheets
Sizes	Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm

Xerox® VersaLink® C400 Color Printer

Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom
OPTIONAL TRAY 2	
Capacity⁵	550 sheets
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom
TOTAL CAPACITY	
Standard Device Capacity⁵	700 sheets
Total Device Capacity⁵	1,250 sheets
PAPER OUTPUT	
Output Capacity⁵	250 sheets
Automatic Two-sided Printing	Standard

DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Xerox® VersaLink® C400 Color Printer

WHAT'S IN THE BOX		
	VersaLink C400 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,000 print capacity ⁶ , Black: 3,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Cyan: 2,500 standard pages ⁶ Magenta: 2,500 standard pages ⁶ Yellow: 2,500 standard pages ⁶ Black: 2,500 standard pages ⁶	106R03502 106R03503 106R03501 106R03500
High Capacity Toner Cartridges	Cyan: 4,800 standard pages ⁶ Magenta: 4,800 standard pages ⁶ Yellow: 4,800 standard pages ⁶ Black: 5,000 standard pages ⁶	106R03514 106R03515 106R03513 106R03512
Extra-High Capacity Toner Cartridges	Cyan: 8,000 standard pages ⁶ Magenta: 8,000 standard pages ⁶ Yellow: 8,000 standard pages ⁶ Black: 10,500 standard pages ⁶	106R03526 106R03527 106R03525 106R03524
ROUTINE MAINTENANCE ITEMS		
Imaging Unit (includes 4 imaging units)	Cyan: 60,000 standard pages ⁷ Magenta: 60,000 standard pages ⁷ Yellow: 60,000 standard pages ⁷ Black: 60,000 standard pages ⁷	108R01121
Waste Cartridge	30,000 pages ⁷	108R01124
ACCESSORIES		
550-sheet Paper Tray		097S04400
Productivity Kit with 320 GB HDD		097S04914
Stand		497K13660
Wireless Network Adapter		497K16750
Internal Card Reader/RFID Kit		497K18120

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



www.ImagingEssentials.com
800.575.1545

